

MAXIMUM 671 KW (900 HP) @ 2300 RPM [PLEASURE CRAFT DUTY]



STANDARD EQUIPMENT

MGX-5096 A

- SAE J617 housing no. 1
- Flexible coupling for 14" flywheel (SAE J620 size 355)
- Electric GP-valve with manual override
- EC050 profile module – interface for engagement signals
- Oil strainer and oil filter

OPTIONS

- EC050 E-Troll module – interface for engagement and trolling signals
- Oil cooler with thermostatic bypass valve
- Companion flange/bolts set
- Monitoring devices to customer's specification
- Mounting brackets
- Live PTO – max. 593 Nm
 - SAE J744 size 127-4, 32-4 (SAE "C", 4-bolt)
- Weight (dry weight with standard equipment)

MGX-5096 A

EC050 E-Troll module – interface for engagement and trolling signals	x
Oil cooler with thermostatic bypass valve	x
Companion flange/bolts set	x
Monitoring devices to customer's specification	x
Mounting brackets	x
Live PTO – max. 593 Nm	
SAE J744 size 127-4, 32-4 (SAE "C", 4-bolt)	x
Weight (dry weight with standard equipment)	236 kg

Specifications subject to change without prior notice in the interest of continual product improvement.

INPUT RATINGS – KILOWATTS (KW) (HORSEPOWER [HP])*

MGX-5096 A	Reduction Ratios :1	Pleasure Craft		Light Duty		Input Speed Limits RPM
		@2100 RPM	@2300 RPM	@2100 RPM	@2300 RPM	
	1.28, 1.52 1.81, 2.04	618 kW (829 hp)	671 kW (900 hp)	560 kW (751 hp)	597 kW (801 hp)	3000 MAX.
	2.48	556 kW (746 hp)	596 kW (799 hp)	520 kW (697 hp)	559 kW (750 hp)	

** Ratings shown are for use with standard right hand rotation engines.*

SERVICE CLASSIFICATION DEFINITIONS

Pleasure Craft [PC]: Up to 500 hours/year, low load factor usage planing hull vessels where typical full engine throttle operation is less than 10% of total time. The balance of operation at 80% of full engine throttle or less. Marine transmissions for use in long-range pleasure cruisers, sportfish charter boats/patrol boats do not qualify for Pleasure Craft Service.

Note: Some revenue producing applications such as Planing Hull Bristol Bay Gillnetter do qualify under Pleasure Craft rating definition.

Light Duty [LD]: Relatively low hour usage (less than 1500 hours per year) where full throttle operation is 2 hours out of 12.

Typical applications include planing hull vessels such as fire boats, sportfish charter boats, and patrol/custom boats. This rating is also applicable to some bow and stern thruster applications.

Intermediate Duty [ID]: Hour usage of up to 2000 hours/year (for models MG-5114 Series and smaller) and up to 3000 hours/year (for models larger than MG-5114 Series) with 50% of the operating time at full engine rating.

Typical applications include planing hull vessels such as ferries, fishing boats, some crew boats, and some displacement hull yachts as well as some bow and stern thruster applications.

Medium Duty [MD]: Hour usage of up to 4000 hours/year with up to 80% of operating time at full engine power. This duty classification is for usage where some variations in engine speed/power occur as part of normal vessel operation.

Typical vessels include mid-water trawlers, crew/supply boats, ferries and some inland water tow boats.

Continuous Duty [CD]: For use in continuous operation with little or no variation in engine speed/power setting.


Typical vessels include fishing trawlers, tow/tug boats and ocean going vessels.

Important Notice: Torsional Vibration: Disregarding propulsion system torsional compatibility could cause damage to components in the drive train resulting in loss of mobility. At minimum, system incompatibility could result in gear clatter at low speeds.

The responsibility for ensuring that the torsional compatibility of the propulsion system is satisfactory rests with the assembler of the drive and driven equipment.

Torsional vibration analysis can be made by the engine builder, marine survey societies, independent consultants and others. Twin Disc is prepared to assist in finding solutions to potential torsional problems that relate to the marine transmission.

Twin Disc, Incorporated reminds users of these products that their safe operation depends on use in compliance with engineering information provided in this bulletin. Users are also reminded that safe operation depends on proper installation, operation and routine maintenance and inspection under prevailing conditions. It is the responsibility of the user (and not Twin Disc, Incorporated) to provide and install guards or safety devices which may be required by recognized safety standards or by the Occupational Safety and Health Act of 1970 and its subsequent provision.



C	190.6 mm (7.50 in)
S	138.8 mm (5.46 in)
F	501.1 mm (19.73 in)
L	265.0 mm (10.43 in)
R	265.0 mm (10.43 in)
A	7°

